NEVADA 2

IT

Morsetto di massa in lamiera di acciaio elettrozincato, contatti in ottone ramato e shunt in rame. Serraggio del cavo con lamella in rame avvolgifili e serracavo in acciaio ramato.

EN

Zinc-plated metal sheet ground clamp, copper-plated brass contacts and copper shunt. Cable fastened with copper winding reel and copper-plated brass tightening plate.

CE **BS 638.5**



CODE	DESCRIZIONE	DESCRIPTION	⌀	X 60%	X 35%	⇔	↓	📦
MRS000018	Morsetto di massa NEVADA 2	NEVADA 2 ground clamp	25 – 35 mm²	200 A	250 A	58 mm	225 g	10

NEVADA 3

IT

Morsetto di massa in lamiera di acciaio elettrozincato. Contatti in ottone ramato e treccia in rame. Serraggio del cavo con lamella in rame avvolgifili e serracavo in acciaio ramato.

EN

Zinc-plated metal sheet ground clamp, copper-plated brass contacts and copper braid. Cable fastened with copper winding reel and copper-plated brass tightening plate.

CE **BS 638.5**



CODE	DESCRIZIONE	DESCRIPTION	⌀	X 60%	X 35%	⇔	↓	📦
MRS000028	Morsetto di massa NEVADA 3	NEVADA 3 ground clamp	50 – 70 mm²	300 A	400 A	73 mm	330 g	10

All trademarks are exclusive property of the respective companies. Data and images are indicative and may be changed in any time without notice. Trafimet Group SpA

NEVADA 5

IT

Morsetto di massa in lamiera di acciaio elettrozincato. Contatti in ottone ramato basculanti e treccia in rame. Serraggio del cavo con lamella in rame avvolgifili e serracavo in ottone.

EN

Zinc-plated metal sheet ground clamp, tilting copper-plated brass contacts and copper braid. Cable fastened with copper winding reel and brass tightening plate.

CE **BS 638.5**



CODE	DESCRIZIONE	DESCRIPTION	⊛	X 60%	X 35%	⇶	⭳	▭
MRS000039	Morsetto di massa NEVADA 5	NEVADA 5 ground clamp	70 – 95 mm²	400 A	500 A	95 mm	590 g	10

NEVADA 6

IT

Morsetto di massa in lamiera di acciaio elettrozincato. Contatti in ottone ramato basculanti e doppia treccia in rame. Serraggio del cavo con lamella in rame avvolgifili e serracavo in ottone.

EN

Zinc-plated metal sheet ground clamp, tilting copper-plated brass contacts and copper double braid. Cable fastened with copper winding reel and brass tightening plate.

CE **BS 638.5**





CODE	DESCRIZIONE	DESCRIPTION	⊛	X 60%	X 35%	⇶	⭳	▭
MRS000050	Morsetto di massa NEVADA 6	NEVADA 6 ground clamp	95 – 120 mm²	500 A	600 A	95 mm	650 g	10

All trademarks are exclusive property of the respective companies. Data and images are indicative and may be changed in any time without notice. Trafimet Group SpA